

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H01H 13/20, 3/12	A1	(11) International Publication Number: WO 00/10183 (43) International Publication Date: 24 February 2000 (24.02.00)
<p>(21) International Application Number: PCT/GB99/02565</p> <p>(22) International Filing Date: 4 August 1999 (04.08.99)</p> <p>(30) Priority Data: 9817527.6 13 August 1998 (13.08.98) GB</p> <p>(71) Applicant (for all designated States except US): CRAIG & DERRICOTT LIMITED [GB/GB]; Hall Lane, Walsall Wood, West Midlands WS9 9DP (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): JONES, David, William [GB/GB]; 46 Reindeer Road, Fazeley, Nr.Tamworth, Staffordshire B78 3SW (GB).</p> <p>(74) Agent: FORRESTER KETLEY & CO.; Chamberlain House, Paradise Place, Birmingham B3 3HP (GB).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>
<p>(54) Title: OPERATING MECHANISM</p> <p>(57) Abstract</p> <p>A mechanism for displacing at least one actuating member (22, 23) in a direction in response to displacement of an operating member (15) in said direction, the mechanism including four elements (24-27) pivotally connected to one another generally in the form of a rhombus, with a pivotable connection (28) between a first two of the elements being displaced by the operating member and the pivotable connection (31) between the other two of the elements being held stationary, the at least one actuating member (22, 23) being engaged by at least one (26, 27) of said elements between the ends thereof. The mechanism is applicable to push-button operated electrical switches.</p> <div data-bbox="933 1165 1380 1816"> </div>		

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 00/10183

PCT/GB99/02565

Title: OPERATING MECHANISM

Description of Invention

This invention relates to an operating mechanism, for effecting displacement of a member (herein called an actuating member) in a direction in response to a displacement of a further member (herein called an operating member) in that direction.

The invention has been devised in relation to push-button operated electrical switches. There are many situations in which push-button operation of electrical switches is required, and in some situations a single push-button may be required to operate several sets of contacts in a single switching unit or a number of switching units assembled in relation to one another so as to be operable from a single push-button. If one or more of such switches are of heavy-duty type, the force required to be exerted by an operator on the push-button may be substantial: such switches characteristically include strong springs to resist movement of their operating members. If switch operation is required frequently, the requirement for an operator repeatedly to press a push button against a strong spring force is potentially hazardous in terms of repetitive strain injury to the operator.

It is well known that a simple lever arrangement can be utilised to provide a mechanical advantage between an actuating member of an electrical switch and an operator's push-button, but this is a bulky arrangement and not readily accommodated in, for example, a control panel incorporating a large number of push-button operated switches adjacent one another.

Accordingly, there is a requirement for an operating mechanism by which a mechanical advantage can be established between an actuating member of a switch and an operator's push-button, but which is simple and compact. It is the object of the present invention to meet, as far as possible, this requirement.

WO 00/10183

PCT/GB99/02565

2

According to the present invention, we provide a mechanism for displacing at least one actuating member in a direction in response to displacement of an operating member in said direction, said mechanism including four elements pivotally connected to one another generally in the form of a rhombus, with the pivotal connection between a first two of said elements being arranged to be displaced in said direction by said operating member, the pivotal connection between the other two of said elements being held stationary, and said at least one actuating member being engaged by at least one of said elements between the ends thereof. Preferably there are two actuating members which are engaged by said other two of said pivotally-connected elements between the ends of said elements.

In a mechanism in accordance with the invention, the arrangement of the four elements in the configuration of a rhombus is such that displacement of the operating member results in a flattening of the rhombus and hence pivotal movement of said other two elements about the point of their pivotal connection to one another which is held stationary. A given displacement of the or each actuating member engaged by one or both of said other two elements requires a much greater displacement of the pivotal connection between the first two of said elements and hence of the operating member which engages said connection. The ratio of the magnitude of such displacements, of course, depends on the exact geometry of the mechanism.

Preferably the operating member comprises or is directly operable by an operator's push-button.

These and other features of the invention will now be described by way of example with reference to the accompanying drawings, of which:-

Figure 1 illustrates the invention in a first operative position, and

Figure 2 illustrates it in a second operative position.

Referring to the drawings, the face of a control panel is indicated at 10 and there is mounted therein a push-button unit indicated generally at 11. The

WO 00/10183

PCT/GB99/02565

3

push-button unit 11 has a bezel 12 and a body 13 which extends through an aperture in the control panel and is somewhat cup-shaped, having a rear portion 14. A push-button having a stem 15 and head 16 is mounted within the body 13, the stem 15 slidably passing through an aperture 17 in the rear part 14 of the body. At its free end, where it protrudes beyond the aperture 17, the stem 15 is fitted with a retaining washer 18, e.g. retained by a circlip.

Beneath the push-button unit 11 and connected thereto by a carrying member indicated generally at 19 there are disposed two electrical switches or contactor units 20, 21. Each of these is of a type having two pairs of contacts, the respective pairs of contacts of the contactor unit 20 being operable by actuating members 22, 23 respectively. The contacts may be normally open or normally closed, or there may be one set of contacts of each type, and they are brought to the respective other condition (open or closed) by depression of the respective actuating members 22, 23. The contactor unit 21 has similar actuating members not shown which protrude into the contactor unit 20 and are also displaced when the actuating members 22, 23 are displaced.

Interposed between the end of the stem 15 and the actuating members 22, 23 there is a mechanism including four elongate elements 24, 25, 26, 27 pivotally connected to one another at 28, 29, 30, 31. The pivotal connection 28 between the elements 24, 25 abuts the end of the stem 15, whilst the pivotal connection 31 between the other two elements 26, 27 is held stationary relative to the connecting member 19. The pivotal connections 29, 30 between the elements 24, 26 and 25, 27 respectively are free to move within the connecting element 19. The connection 28 between the elements 24, 25 is guided for linear movement relative to the carrying member 19, e.g. by having a hinge pin whose opposite ends engage in respective slots in opposed sides of the carrying members.

The actuating members 22, 23 abut the elements 26, 27 between the ends thereof.

WO 00/10183

PCT/GB99/02565

4

The elements 24 to 27 are thus pivotally connected to one another generally in the configuration of a rhombus, and when the push-button 15, 16 is depressed the rhombus is flattened as shown in Figure 2 of the drawings. It will be appreciated from a consideration of Figure 2 that a substantial displacement of the push-button 15, 16 has resulted in a proportionate but lesser displacement of the actuating members 22, 23, with the ratio between such displacements dependent on the exact geometry of the arrangement of the elements 24, 27 and, particularly, where the actuating members 22, 23 engage the elements 26, 27. In any event, a substantial mechanical advantage is established, so that considerably less force has to be exerted by the operator on the push-button 15, 16 than the force which would be required to be exerted if the actuating members 22, 23 were engaged directly by the end of the stem 15.

Since in a practical installation several contactor units as 20, 21 may be connected beneath one another for operation by a single push-button, and since a considerable force might then be required to be exerted particularly if they are heavy duty units, the invention provides a particularly neat and compact arrangement by which the force required to be exerted by an operator can be reduced.

The elements 24 to 27 may be individual rigid elements, e.g. of sheet metal or an appropriate plastics material, pivotally connected by appropriate hinge arrangements at 28 to 31. An alternative possibility is that such elements of an appropriate plastics material may be pivotally connected by "living hinge" arrangements, i.e. portions wherein the cross-sectional dimension of the material is sufficiently small to pivotally connect the elements to one another by flexing of the material. It is envisaged that an assembly of such elements might be manufactured as a flat strip of the elements in line with one another, with three integral "living hinge" formations therebetween, the outermost ends of the end elements being provided with formations enabling them to be

WO 00/10183

PCT/GB99/02565

5

pivotally connected together after the strip of elements has been bent into the rhombus configuration.

The features disclosed in the foregoing description, or the accompanying drawing, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, may, separately or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

WO 00/10183

PCT/GB99/02565

6

CLAIMS:-

1. A mechanism for displacing at least one actuating member in a direction in response to displacement of an operating member in said direction, said mechanism including four elements pivotally connected to one another generally in the form of a rhombus, with a pivotal connection between a first two of said elements being arranged to be displaced in said direction by said operating member, the pivotal connection between the other two of said elements being held stationary, and said at least one actuating member being engaged by at least one of said elements between the ends thereof.
2. A mechanism according to Claim 1 comprising two actuating members engaged by said other two of said elements.
3. A mechanism according to Claim 1 or Claim 2 wherein the operating member comprises or is directly operable by an operator's push-button.
4. A mechanism according to any one of the preceding claims wherein said four elements comprise separate components, pivotally connected by hinge means.
5. A mechanism according to any one of Claims 1 to 3 wherein at least two of said four elements comprise plastics components integrally connected to one another by "living hinge" formations.
6. An electrical switch assembly comprising switching means having at least one actuating member and a mechanism according to any one of the preceding claims for displacing said at least one actuating member.

WO 00/10183

PCT/GB99/02565

7

7. A mechanism, or a switch assembly incorporating same, substantially as hereinbefore described with reference to the accompanying drawings.

WO 00/10183

PCT/GB99/02565

1/1




FIG 2




FIG 1

INTERNATIONAL SEARCH REPORT

International Application No.

PC., GB 99/02565

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H01H13/20 H01H3/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category ¹	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 562 203 A (MOCHIZUKI ISAO) 8 October 1996 (1996-10-08) abstract; figure 1	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.¹ Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "S" document member of the same patent family

Date of the actual completion of the international search

8 November 1999

Date of mailing of the international search report

17/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Mausser, T

Form PCT-ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC, GB 99/02565

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5562203 A	08-10-1996	JP 8124453 A	17-05-1996

Form PCT/ISA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.